

NOTES:

*GRIDS OVER STRUCTURES @ 32" O.C. TO SUPPORT A MAX LOAD OF 300 LBS PER SQ. FT. ALL GRIDS WITH LEVEL BASE FRAME TO SUPPORT A 400 LB. ROLLING LOAD. LARGER LOADING MAY BE ACCOMMODATED. CONTACT C/S

*PLEASE VERIFY TRAFFIC DIRECTION.

SALES WITH SPECIFIC LOADING REQUIREMENTS.

*MAXIMUM MODULE SIZE OF GRID NOT TO EXCEED 12'-0" [3.6M] IN WIDTH (DIM "A") & 3'-0" [.91M] IN LENGTH T.D. (DIM "B").

*ALL SURFACES IN CONTACT WITH MASONRY ARE TO RECEIVE A

*MITERED FRAME CORNERS ARE NOT AVAILABLE.

COAT OF ZINC CHROMATE PRIMER.

*WITH OPTION #2, THE ANCHOR LEG IS CUT OFF TO ALLOW FOR FLUSH MOUNTING IN A FORMED PIT.

*DUE TO 1 1/2" MODULE OF PEDIGRID, INSIDE OF FRAME DIMENSION SHOULD BE CHANGED ONLY IN INCREMENTS OF 1 1/2" [38.1mm] TO AVOID THE USE OF FILLER BARS.

*ADDITIONAL SPECIFICATIONS ARE CONTAINED IN THE LATEST C/S CATALOG OR AT C-SGROUP.COM AND ARE CONSIDERED PART OF

THIS TRANSMITTAL.

M AND ARE	CONOIDENEDTA	
The Park	EAGLE	MA
	& FLOOR PR	ODUCT

BY

BY

										AND RESIDENCE OF THE PARTY OF THE PARTY.	
ALL	QTY	MARK#	LOCATION	MODEL	DIM 'A'	DIM 'B'	FINISH	REMARKS	PROJECT:		
I ^ L					WIDTH	LENGTH			LOCATION:		
IE									CONTRACTOR:		
VERIF											
ΙΨI									AGENT: S		SHT:
1											
									DRG. BY:	DATE:	JOB NO.:
ďΙ									1		
Щ									1		
PLEASE											